

Acton

7062.01 - 7062.39



Product Upholstery

Description

Strong upholstery fabric in a melange look, in a wide range of colours

Composition

87% recycled polyester FR / 13% polyester FR

Width

± 141 cm, ± 56 inches

Weight

± 605 gr/m¹, ± 20 oz/yd¹

Flame retardancy

**BS 5852 , Crib 5
Cal TB 117-2013, section 1 , Pass
DIN 4102 , B1
EN 1021/1-2 , Pass
IMO 2010 FTP part 8 , Pass
NF P 92/503-507 , M1
NFPA 260 , Class 1**

Abrasion

**ASTM D3597/D4157 (#10 cotton duck) ,
100.000 double rubs Wyzenbeek
ISO 12947-2 , 90.000 rubs Martindale**

Pilling

**ASTM D3511
5 (scale 1-5)
ISO 12945-2
4 (scale 1-5)**

Colorfastness to crocking

AATCC 8

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105 X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 opt.1 or 16.3 opt. 3

4 (scale 1-5)

ISO 105 B02

6 (scale 1-8)

Seam slippage

ASTM D4034

109 lbs warp / 86 lbs weft

ISO 13936-2

3.7 mm warp / 3.7 mm weft

Breaking strength

ASTM D5034

263 lbs warp / 345 lbs weft

ISO 13934-1

1380 N warp / 1790 N weft

Labels



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI

Care & Maintenance



Shrinkage

Shrinkage 70°

-2.7% warp / -0.6% weft

Acton

7062.01 - 7062.39
