

Acton

7062.01 - 7062.39



Prodotto
upholstery

Descrizione
**Strong upholstery fabric in a melange look,
in a wide range of colours**

Composizione
**87% recycled polyester FR / 13% polyester
FR**

Larghezza
± 141 cm, ± 56 inches

Peso
± 605 gr/m¹, ± 20 oz/yd¹

Resistenza al fuoco
**BS 5852 , Crib 5
Cal TB 117-2013, section 1 , Pass
DIN 4102 , B1
EN 1021/1-2 , Pass
IMO 2010 FTP part 8 , Pass
NF P 92/503-507 , M1
NFPA 260 , Class 1**

Resistenza all'abrasione
**ASTM D3597/D4157 (#10 cotton duck) ,
100.000 double rubs Wyzenbeek
ISO 12947-2 , 90.000 rubs Martindale**

Resistenza al pilling
**ASTM D3511
5 (scale 1-5)
ISO 12945-2
4 (scale 1-5)**

Solidità allo sfregamento

AATCC 8
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105 X12
4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Resistenza alla luce
AATCC 16.2 opt.1 or 16.3 opt. 3
4 (scale 1-5)
ISO 105 B02
6 (scale 1-8)

Resistenza al taglio cucitura
ASTM D4034
109 lbs warp / 86 lbs weft
ISO 13936-2
3.7 mm warp / 3.7 mm weft

Resistenza alla trazione
ASTM D5034
263 lbs warp / 345 lbs weft
ISO 13934-1
1380 N warp / 1790 N weft

Etichette



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI

Cura & Manutenzione



Restringimento
Shrinkage 70°
-2.7% warp / -0.6% weft

Acton

7062.01 - 7062.39
