

Acton

7062.01 - 7062.39



Product
upholstery

Omschrijving
Sterke meubelstof in melange optiek, in breed kleurengamma

Samenstelling
87% recycled polyester FR / 13% polyester FR

Breedte
± 141 cm, ± 56 inches

Gewicht
± 605 gr/m¹, ± 20 oz/yd¹

Brandwerendheid
BS 5852 , Crib 5
Cal TB 117-2013, section 1 , Pass
DIN 4102 , B1
EN 1021/1-2 , Pass
IMO 2010 FTP part 8 , Pass
NF P 92/503-507 , M1
NFPA 260 , Class 1

Slijtvastheid
ASTM D3597/D4157 (#10 cotton duck) ,
100.000 double rubs Wyzenbeek
ISO 12947-2 , 90.000 rubs Martindale

Pilling
ASTM D3511
5 (scale 1-5)
ISO 12945-2
4 (scale 1-5)

Wrijftechtheid
AATCC 8
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105 X12
4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Lichtechtheid
AATCC 16.2 opt.1 or 16.3 opt. 3
4 (scale 1-5)
ISO 105 B02
6 (scale 1-8)

Naadschuifweerstand
ASTM D4034
109 lbs warp / 86 lbs weft
ISO 13936-2
3.7 mm warp / 3.7 mm weft

Treksterkte
ASTM D5034
263 lbs warp / 345 lbs weft
ISO 13934-1
1380 N warp / 1790 N weft

Keurmerken



Reiniging & Onderhoud



Krimp
Shrinkage 70°
-2.7% warp / -0.6% weft

Acton

7062.01 - 7062.39
