

Arches

7066.01 - 7066.17



Produit
upholstery

Description
Structure de tissage textile dynamique

Composition
Enduction vinylique, tricot polyester/coton

Largeur
± 137-140 cm, ± 54-55 inches

Poids
± 800 gr/m², ± 36 oz/yd¹

Non feu
BS 5852 , Crib 5
Cal TB 117-2013, section 1 , Pass
DIN 4102 , B2
EN 1021/1-2 , Pass
IMO 2010 FTP part 8 , Pass
NF P 92/503-507 , M2
NFPA 260 , Class 1

Résistance à l'abrasion
ASTM D3597/D4157 (#10 cotton duck) ,
100.000 double rubs Wyzenbeek
ISO 12947-2 , > 300.000 rubs Martindale

Résistance au frottement
AATCC 8
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105 X12
5 (scale 1-5) wet / 5 (scale 1-5) dry

Solidité lumière
ISO 105 B02
7 (scale 1-8)

Étiquettes



USCG –
EU MRA
0038

vinyl ^{plus}
COMMITTED TO
SUSTAINABLE DEVELOPMENT

Arches

7066.01 - 7066.17

7066.01 7066.02 7066.03 7066.04 7066.05 7066.06 7066.07 7066.08 7066.09
7066.10 7066.11 7066.12 7066.13 7066.14 7066.15 7066.16 7066.17