

Bedra+Print

8061.01



Produit
curtain

Description
Rideau imprimable obscurcissant soyeux

Composition
100% polyester ignifuge

Largeur
± 290 cm, ± 114 inches

Poids
± 782 gr/m¹, ± 25 oz/yd¹

Confort Visuel & Thermique
AATCC 148
Test available
EN 410/EN 14501
Test available

Non feu
BS 5867-2 , Type C
CAN/ULC S109 , Pass
DIN 4102 , B1
EN 13773 , Class 1
IMO 2010 FTP part 7 , Pass
NF P 92/503-507 , M1
NFPA 701 (meth. 1 or 2) , Pass
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1

Résistance au frottement
AATCC 8 (solids)
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105-X12
5 (scale 1-5) wet / 5 (scale 1-5) dry

Solidité lumière
AATCC 16.2 option 1 or 16.3 opt 3
4-5 (scale 1-5)
ISO 105-B02
6 (scale 1-8)

Résistance au glissement à la couture
ASTM D434
43.5 lbs warp / 48 lbs weft


Étiquettes



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

Entretien & Maintenance



Rétrécissement
Shrinkage 30°
-0.4% warp / -1.4% weft
Shrinkage 70°
-2.5% warp / -1.5% weft

Bedra+Print

8061.01



8061.01