

Bray+Print

8065.01



Product
curtain

Omschrijving

Kamerhoge curtain+print black out met een richtingloze weefstructuur

Samenstelling

100% flame retardant polyester acrylic coating

Breedte

± 280 cm, ± 110 inches

Gewicht

± 1075 gr/m², ± 35 oz/yd²

Visueel & Thermisch comfort

AATCC 148

Test available

EN 410/EN 14501

Test available

Brandwerendheid

BS 5867-2 , Type B

CAN/ULC S109 , Pass

DIN 4102 , B1

EN 13773 , Class 1

IMO 2010 FTP part 7 , Pass

NFPA 701 (meth. 1 or 2) , Pass

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

Wrijftechtheid

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Lichtechtheid

AATCC 16.2 option 1 or 16.3 opt 3

2.5 (scale 1-5)

ISO 105-B02

5 (scale 1-8)

Naadschuifweerstand

ASTM D434

44 lbs warp / 49.5 lbs weft

Keurmerken



USCG -
EU MRA
0038



Baustoffklasse schwerenflammbar
DIN 4102, B1

Reiniging & Onderhoud



Krimp

Shrinkage 30°

-0.9% warp / -0.6% weft

Shrinkage 70°

-1.5% warp / -1.2% weft

Bray+Print

8065.01

8065.01