


Burton

7056.01 - 7056.23



Product
upholstery

Description
Two-tone woven unpatterned fabric with a blended effect

Composition
100% flame retardant polyester

Width
± 140 cm, ± 55 inches

Weight
± 763 gr/m², ± 25 oz/yd²

Flame retardancy
EN 1021/1-2 , Pass
BS 5852 , Crib 5
NF P 92/503-507 or NF D 60-013 , M1
DIN 4102 , B1
Cal TB 117-2013, section 1 , Pass
IMO 2010 FTP part 8 , Pass
NFPA 260 , Class 1

Abrasion
ISO 12947-2 , 80.000 rubs martindale
ASTM D3597/D4157 (#10 cotton duck) ,
100.000 double rubs wyzenbeek

Pilling
ISO 12945-2
4 (scale 1-5)
ASTM D3511
4 (scale 1-5)

Colorfastness to crocking
ISO 105 X12
wet 4 - 5 (scale 1-5) / dry 4 - 5 (scale 1-5)
AATCC 8
wet 5 (scale 1-5) / dry 5 (scale 1-5)

Colorfastness to light
ISO 105 B02
6 - 7 (scale 1-8)
AATCC 16.2 opt.1 or 16.3 opt. 3
4.5 (scale 1-5)

Seam slippage
ISO 13936-2 - warp
3 mm
ISO 13936-2 - weft
2.7 mm
ASTM D4034 - warp
101 lbs
ASTM D4034 - weft
107 lbs

Breaking strength
ASTM D5034 - warp
365 lbs
ASTM D5034 - weft
289 lbs

Labels



USCG -
EU MRA
0038



STANDARD
100
S07-0023
Hohenstein HTTI

Care & Maintenance



Burton

7056.01 - 7056.23

Shrinkage

Shrinkage 30° - warp

-0.7

Shrinkage 30° - weft

-0.6

Shrinkage 70° - warp

-1.8

Shrinkage 70° - weft

-2.2

Burton

7056.01 - 7056.23
