

# Burton

7056.01 - 7056.23



Produit  
**upholstery**

Description  
**Two-tone woven unpatterned fabric with a blended effect**

Composition  
**100% flame retardant polyester**

Largeur  
**± 140 cm, ± 55 inches**

Poids  
**± 763 gr/m<sup>1</sup>, ± 25 oz/yd<sup>1</sup>**

Non feu  
**EN 1021/1-2 , Pass**  
**BS 5852 , Crib 5**  
**NF P 92/503-507 or NF D 60-013 , M1**  
**DIN 4102 , B1**  
**Cal TB 117-2013, section 1 , Pass**  
**IMO 2010 FTP part 8 , Pass**  
**NFPA 260 , Class 1**

Résistance à l'abrasion  
**ISO 12947-2 , 80.000 rubs martindale**  
**ASTM D3597/D4157 (#10 cotton duck) ,**  
**100.000 double rubs wyzenbeek**

Boulochage  
**ISO 12945-2**  
4 (scale 1-5)  
**ASTM D3511**  
4 (scale 1-5)

Résistance au frottement  
**ISO 105 X12**  
wet 4 - 5 (scale 1-5) / dry 4 - 5 (scale 1-5)  
**AATCC 8**  
wet 5 (scale 1-5) / dry 5 (scale 1-5)

Solidité lumière  
**ISO 105 B02**  
6 - 7 (scale 1-8)  
**AATCC 16.2 opt.1 or 16.3 opt. 3**  
4.5 (scale 1-5)

Résistance au glissement à la couture  
**ISO 13936-2 - warp**  
3 mm  
**ISO 13936-2 - weft**  
2.7 mm  
**ASTM D4034 - warp**  
101 lbs  
**ASTM D4034 - weft**  
107 lbs

Résistance à la traction  
**ASTM D5034 - warp**  
365 lbs  
**ASTM D5034 - weft**  
289 lbs

Étiquettes



USCG -  
EU MRA  
0038



STANDARD  
100  
S07-0023  
Hohenstein HTTI

Entretien & Maintenance



# Burton

7056.01 - 7056.23

---

Rétrécissement

**Shrinkage 30° - warp**

-0.7

**Shrinkage 30° - weft**

-0.6

**Shrinkage 70° - warp**

-1.8

**Shrinkage 70° - weft**

-2.2

# Burton

7056.01 - 7056.23

---