

Burton

7056.01 - 7056.23



产品

upholstery

描述

Two-tone woven unpatterned fabric with a blended effect

成分

100% flame retardant polyester

宽幅

± 140 cm, ± 55 inches

重量

± 763 gr/m², ± 25 oz/yd²

阻燃

EN 1021/1-2 , Pass

BS 5852 , Crib 5

NF P 92/503-507 or NF D 60-013 , M1

DIN 4102 , B1

Cal TB 117-2013, section 1 , Pass

IMO 2010 FTP part 8 , Pass

NFPA 260 , Class 1

耐磨性

ISO 12947-2 , 80.000 rubs martindale

ASTM D3597/D4157 (#10 cotton duck) ,

100.000 double rubs wyzenbeek

起毛指数

ISO 12945-2

4 (scale 1-5)

ASTM D3511

4 (scale 1-5)

耐摩擦褪色

ISO 105 X12

wet 4 - 5 (scale 1-5) / dry 4 - 5 (scale 1-5)

AATCC 8

wet 5 (scale 1-5) / dry 5 (scale 1-5)

耐光照褪色

ISO 105 B02

6 - 7 (scale 1-8)

AATCC 16.2 opt.1 or 16.3 opt. 3

4.5 (scale 1-5)

耐滑缝

ISO 13936-2 - warp

3 mm

ISO 13936-2 - weft

2.7 mm

ASTM D4034 - warp

101 lbs

ASTM D4034 - weft

107 lbs

抗断裂强度

ASTM D5034 - warp

365 lbs

ASTM D5034 - weft

289 lbs

标签



USCG -
EU MRA
0038



STANDARD
100
S07-0023
Hohenstein HTTI

保养与维护



Burton

7056.01 - 7056.23

收缩率

Shrinkage 30° - warp

-0.7

Shrinkage 30° - weft

-0.6

Shrinkage 70° - warp

-1.8

Shrinkage 70° - weft

-2.2

Burton

7056.01 - 7056.23
