

Clare

8052.01 - 8052.24



Producto

curtain

Descripción

Estructura de malla transparente abierta

Composición

100% poliéster ignífugo

Anchura

± 300 cm, ± 118 inches

Peso

± 174 gr/m¹, ± 6 oz/yd¹

Confort Visual & Térmico

EN 410/EN 14501

Test available

Combustión retardada

BS 5867-2 , Type C

CAN/ULC S109 , Pass

DIN 4102 , B1

EN 13773 , Class 1

IMO 2010 FTP part 7 , Pass

NF P 92/503-507 , M1

NFPA 701 (meth. 1 or 2) , Pass

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

Resistencia al frotamiento

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Insensibilidad a la luz

AATCC 16.2 option 1 or 16.3 opt 3

5 (scale 1-5)

ISO 105-B02

6 (scale 1-8)


Etiquetas



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein RTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

Cuidado & Mantenimiento



Contracción

Shrinkage 30°

-1.6% warp / -1.4% weft

Shrinkage 70°

-2% warp / -2% weft

Clare

8052.01 - 8052.24

8052.01	8052.02	8052.03	8052.04	8052.05	8052.06	8052.07	8052.08	8052.09
8052.10	8052.11	8052.12	8052.13	8052.14	8052.15	8052.16	8052.17	8052.18
8052.19	8052.20	8052.21	8052.22	8052.23	8052.24			