


Colour Connect

7078.01 - 7078.43



Product

Upholstery

Description

Plain upholstery fabric in a large colour range

Composition

100% recycled polyester FR

Width

± 150 cm, ± 59 inches

Weight

± 435 gr/m², ± 14 oz/yd²

Flame retardancy

BS 5852 , Crib 5

Cal TB 117-2013, section 1 , Pass

DIN 4102 , B1

EN 1021/1-2 , Pass

IMO 2010 FTP part 8 , Pass

NF D 60-013 , Pass

NFPA 260 , Class 1

Abrasion

ASTM D3597/D4157 (#10 cotton duck) ,

100.000 double rubs Wyzenbeek

ISO 12947-2 , 60.000 rubs Martindale

Pilling

ASTM D3511

5 (scale 1-5)

ISO 12945-2

4-5 (scale 1-5)

Colorfastness to crocking

AATCC 8

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105 X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 opt.1 or 16.3 opt. 3

5 (scale 1-5)

ISO 105 B02

6 (scale 1-8)

Seam slippage

ASTM D4034

121 lbf warp / 109 lbf weft

ISO 13936-2

3.3 mm warp / 2.3 mm weft

Breaking strength

ASTM D5034

268 lbf warp / 260 lbf weft

ISO 13934-1

1350 N warp / 1390 N weft

Labels



USCG –
EU MRA
0038



STANDARD
100
S21-3365
Hohenstein HTTI

Care & Maintenance



Shrinkage

Shrinkage 70°

-2% warp / -1.5% weft

Colour Connect

7078.01 - 7078.43

