

# Dolin

8048.01 - 8048.09



**Product**  
curtain

**Omschrijving**  
Licht gestructureerde melange

**Samenstelling**  
100% brandvertragend polyester

**Breedte**  
± 140 cm, ± 55 inches

**Gewicht**  
± 407 gr/m<sup>2</sup>, ± 13 oz/yd<sup>2</sup>

**Geluidsabsorptie**  
ISO 354, alpha w  
0.85 (pleated)

**Visueel & Thermisch comfort**  
EN 410/EN 14501  
Test available

**Brandwerendheid**  
BS 5867-2 , Type C  
CAN/ULC S109 , Pass  
DIN 4102 , B1  
EN 13773 , Class 1  
IMO 2010 FTP part 7 , Pass  
NF P 92/503-507 , M1  
NFPA 701 (meth. 1 or 2) , Pass  
Übereinstimmung , Pass  
UNI VF 8456-8457 , Classe 1

**Wrijfechtheid**  
AATCC 8 (solids)  
5 (scale 1-5) wet / 5 (scale 1-5) dry  
ISO 105-X12  
4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

**Lichtecheit**  
AATCC 16.2 option 1 or 16.3 opt 3  
5 (scale 1-5)  
ISO 105-B02  
6 (scale 1-8)

**Naadschuifweerstand**  
ASTM D434  
32 lbs warp / 30 lbs weft  
ISO 13936-2  
5.5 mm warp / 4.7 mm weft

**Keurmerken**



USCG -  
EU MRA  
0038



STANDARD  
100  
507-0023  
Hohenstein HTTI



Baustoffklasse schwerentflammbar  
DIN 4102, B1

**Reiniging & Onderhoud**



**Krimp**  
Shrinkage 30°  
-2% warp / -1% weft  
Shrinkage 70°  
-2.8% warp / -2% weft

# Dolin

8048.01 - 8048.09

---

8048.01 8048.02 8048.03 8048.04 8048.05 8048.06 8048.07 8048.08 8048.09