

Dolin

8048.01 - 8048.09



产品

curtain

描述

浅色混纺织物

成分

100% 阻燃聚酯纤维

宽幅

± 140 cm, ± 55 inches

重量

± 407 gr/m², ± 13 oz/yd²

吸声降噪

ISO 354, alpha w
0.85 (pleated)

视觉及热舒适控制

EN 410/EN 14501
Test available

阻燃

BS 5867-2, Type C
CAN/ULC S109, Pass
DIN 4102, B1
EN 13773, Class 1
IMO 2010 FTP part 7, Pass
NF P 92/503-507, M1
NFPA 701 (meth. 1 or 2), Pass
Übereinstimmung, Pass
UNI VF 8456-8457, Classe 1

耐摩擦褪色

AATCC 8 (solids)
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105-X12
4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

耐光照褪色

AATCC 16.2 option 1 or 16.3 opt 3
5 (scale 1-5)
ISO 105-B02
6 (scale 1-8)

耐滑缝

ASTM D434
32 lbs warp / 30 lbs weft
ISO 13936-2
5.5 mm warp / 4.7 mm weft

标签



USCG -
EU MRA
0038



STANDARD
100
S07-0023
Hohenstein HTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

保养与维护



收缩率

Shrinkage 30°
-2% warp / -1% weft
Shrinkage 70°
-2.8% warp / -2% weft

Dolin

8048.01 - 8048.09

8048.01 8048.02 8048.03 8048.04 8048.05 8048.06 8048.07 8048.08 8048.09