

Elba

8069.01 - 8069.20



Product
curtain

Omschrijving

Black out met gerasterde melange look

Samenstelling

100% flame retardant polyester acrylic coating

Breedte

± 277 cm, ± 109 inches

Gewicht

± 1075 gr/m¹, ± 35 oz/yd¹

Geluidsabsorptie

ISO 354, alpha w
0.35

Visueel & Thermisch comfort

AATCC 148

Test available

EN 410/EN 14501

Test available

Brandwerendheid

BS 5867-2 , Type B
CAN/ULC S109 , Pass
DIN 4102 , B1

EN 13773 , Class 1

IMO 2010 FTP part 7 , Pass

NFPA 701 (meth. 1 or 2) , Pass

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

Wrijfechtheid

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Lichtechtheid

AATCC 16.2 option 1 or 16.3 opt 3

2.5 (scale 1-5)

ISO 105-B02

5 (scale 1-8)

Naadschuifweerstand

ASTM D434

44 lbs warp / 49.5 lbs weft

Keurmerken



USCG -
EU MRA
0038



Baustoffklasse schwerentflammbar
DIN 4102, B1

Reiniging & Onderhoud



Krimp

Shrinkage 30°

-0.9% warp / -0.6% weft

Shrinkage 70°

-1.5% warp / -1.2% weft

Elba

8069.01 - 8069.20

8069.01	8069.02	8069.03	8069.04	8069.05	8069.06	8069.07	8069.08	8069.09
8069.10	8069.11	8069.12	8069.13	8069.14	8069.15	8069.16	8069.17	8069.18
8069.19	8069.20							