

Faray

8058.01 - 8058.18



Product
curtain

Description
Ton sur ton dessin of "swirling" lines in the length

Composition
100% flame retardant polyester

Width
± 140 cm, ± 55 inches

Weight
± 312 gr/m², ± 10 oz/yd²

Visual & Thermal comfort
EN 410/EN 14501
Test available

Flame retardancy
NFPA 701 (meth. 1 or 2) , Pass
EN 13773 , Class 1
BS 5867-2 , Type C
NF P 92/503-507 , M1
DIN 4102 , B1
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1
CAN/ULC S109 , Pass
IMO 2010 FTP part 7 , Pass

Colorfastness to crocking
ISO 105-X12
wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)
AATCC 8 (solids)
wet 5 (scale 1-5) / dry 5 (scale 1-5)

Colorfastness to light
ISO 105-B02
6-7 (scale 1-8)
AATCC 16.2 option 1 or 16.3 opt 3
5 (scale 1-5)

Seam slippage
ASTM D434 - warp
40.5 lbs
ASTM D434 - weft
58 lbs

Labels



USCG -
EU MRA
0038



STANDARD
100
S07-0023
Hohenstein RTTI



Baustoffklasse schwerenflammbar
DIN 4102, B1

Care & Maintenance



Shrinkage
Shrinkage 30° - warp
-0.2
Shrinkage 30° - weft
-0.2
Shrinkage 70° - warp
-0.9
Shrinkage 70° - weft
-0.6

Faray

8058.01 - 8058.18
