

Faray

8058.01 - 8058.18



Producto
curtain

Descripción
Ton sur ton dessin of “swirling” lines in the length

Composición
100% flame retardant polyester

Anchura
± 140 cm, ± 55 inches

Peso
± 312 gr/m¹, ± 10 oz/yd¹

Confort Visual & Térmico
EN 410/EN 14501
Test available

Combustión retardada
NFPA 701 (meth. 1 or 2) , Pass
EN 13773 , Class 1
BS 5867-2 , Type C
NF P 92/503-507 , M1
DIN 4102 , B1
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1
CAN/ULC S109 , Pass
IMO 2010 FTP part 7 , Pass

Resistencia al frotamiento
ISO 105-X12
wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)
AATCC 8 (solids)
wet 5 (scale 1-5) / dry 5 (scale 1-5)

Insensibilidad a la luz
ISO 105-B02
6-7 (scale 1-8)
AATCC 16.2 option 1 or 16.3 opt 3
5 (scale 1-5)

Resistencia al deslizamiento de costuras
ASTM D434 - warp
40.5 lbs
ASTM D434 - weft
58 lbs


Etiquetas



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein RTT



Baustoffklasse schwerentflammbar
DIN 4102, B1

Cuidado & Mantenimiento



Contracción
Shrinkage 30° - warp
-0.2
Shrinkage 30° - weft
-0.2
Shrinkage 70° - warp
-0.9
Shrinkage 70° - weft
-0.6

Faray

8058.01 - 8058.18
