

Faray

8058.01 - 8058.18



Prodotto

curtain

Descrizione

Ton sur ton dessin of "swirling" lines in the length

Composizione

100% flame retardant polyester

Larghezza

± 140 cm, ± 55 inches

Peso

± 312 gr/m¹, ± 10 oz/yd¹

Comfort Visivo & Termico

EN 410/EN 14501

Test available

Resistenza al fuoco

NFPA 701 (meth. 1 or 2) , Pass

EN 13773 , Class 1

BS 5867-2 , Type C

NF P 92/503-507 , M1

DIN 4102 , B1

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

CAN/ULC S109 , Pass

IMO 2010 FTP part 7 , Pass

Solidità allo sfregamento

ISO 105-X12

wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)

AATCC 8 (solids)

wet 5 (scale 1-5) / dry 5 (scale 1-5)

Resistenza alla luce

ISO 105-B02

6-7 (scale 1-8)

AATCC 16.2 option 1 or 16.3 opt 3

5 (scale 1-5)

Resistenza al taglio cucitura

ASTM D434 - warp

40.5 lbs

ASTM D434 - weft

58 lbs

Etichette



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein RTT



Baustoffklasse schwerentflammbar
DIN 4102, B1

Cura & Manutenzione



Restringimento

Shrinkage 30° - warp

-0.2

Shrinkage 30° - weft

-0.2

Shrinkage 70° - warp

-0.9

Shrinkage 70° - weft

-0.6

Faray

8058.01 - 8058.18
