

# Faray

8058.01 - 8058.18



## 产品

curtain

## 描述

Ton sur ton dessin of "swirling" lines in the length

## 成分

100% flame retardant polyester

## 宽幅

± 140 cm, ± 55 inches

## 重量

± 312 gr/m<sup>2</sup>, ± 10 oz/yd<sup>2</sup>

## 视觉及热舒适控制

EN 410/EN 14501

Test available

## 阻燃

NFPA 701 (meth. 1 or 2) , Pass

EN 13773 , Class 1

BS 5867-2 , Type C

NF P 92/503-507 , M1

DIN 4102 , B1

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

CAN/ULC S109 , Pass

IMO 2010 FTP part 7 , Pass

## 耐摩擦褪色

ISO 105-X12

wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)

AATCC 8 (solids)

wet 5 (scale 1-5) / dry 5 (scale 1-5)

## 耐光照褪色

ISO 105-B02

6-7 (scale 1-8)

AATCC 16.2 option 1 or 16.3 opt 3

5 (scale 1-5)

## 耐滑缝

ASTM D434 - warp

40.5 lbs

ASTM D434 - weft

58 lbs

## 标签



USCG -  
EU MRA  
0038



STANDARD  
100  
S07-0023  
Hohenstein HTTI



Baustoffklasse schwerenflammbar  
DIN 4102, B1

## 保养与维护



## 收缩率

Shrinkage 30° - warp

-0.2

Shrinkage 30° - weft

-0.2

Shrinkage 70° - warp

-0.9

Shrinkage 70° - weft

-0.6

# Faray

8058.01 - 8058.18

---