

Hestan

7035.01 - 7035.30



Product

Upholstery

Description

A coarse semi unpatterned weave

Composition

> 37% recycled polyester FR / < 63% polyester FR

Width

± 140 cm, ± 55 inches

Weight

± 570 gr/m¹, ± 18 oz/yd¹

Flame retardancy

BS 5852 , Crib 5

Cal TB 117-2013, section 1 , Pass

DIN 4102 , B1

EN 1021/1-2 , Pass

IMO 2010 FTP part 8 , Pass

NF P 92/503-507 , M1

Abrasion

ASTM D3597/D4157 (#10 cotton duck) , 100.000 double rubs Wyzenbeek

ISO 12947-2 , 60.000 rubs Martindale

Pilling

ASTM D3511

4-5 (scale 1-5)

ISO 12945-2

4-5 (scale 1-5)

Colorfastness to crocking

AATCC 8

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105 X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 opt.1 or 16.3 opt. 3

5 (scale 1-5)

ISO 105 B02

6 (scale 1-8)

Seam slippage

ASTM D4034

83 lbf warp / 91 lbf weft

ISO 13936-2

2.7 mm warp / 2.7 mm weft

Breaking strength

ASTM D5034

353 lbs warp / 377 lbs weft

Labels



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein RTT

Care & Maintenance



Shrinkage

Shrinkage 30°

-1.5% warp / -1.5% weft

Shrinkage 70°

-2.9% warp / -3.0% weft

Hestan

7035.01 - 7035.30

7035.01	7035.02	7035.03	7035.04	7035.05	7035.06	7035.07	7035.08	7035.09
7035.10	7035.11	7035.12	7035.13	7035.14	7035.15	7035.16	7035.17	7035.18
7035.19	7035.20	7035.21	7035.22	7035.23	7035.24	7035.25	7035.26	7035.27
7035.28	7035.29	7035.30						