

Lamu

7051.01 - 7051.30



Product
upholstery

Omschrijving
Viltten wolkwaliteit met structuur

Samenstelling
75% post-consumer recycled wol / 25% polyester

Breedte
± 150 cm, ± 59 inches

Gewicht
± 660 gr/m¹, ± 21 oz/yd¹

Brandwerendheid
BS 5852 , Crib 5
Cal TB 117-2013, section 1 , Pass
DIN 4102 , B2
EN 1021/1-2 , Pass
IMO 2010 FTP part 8 , Pass
NF D 60-013 , Pass
NFPA 260 , Class 1

Slijtvastheid
ASTM D3597/D4157 (#10 cotton duck) ,
>30.000 double rubs Wyzenbeek
ISO 12947-2 , >100.000 rubs Martindale

Pilling
ASTM D3511
3 (scale 1-5)
ISO 12945-2
4 (scale 1-5)

Wrijfechtheid
AATCC 8
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105 X12
5 (scale 1-5) wet / 5 (scale 1-5) dry

Lichtechtheid
AATCC 16.2 opt.1 or 16.3 opt. 3
5 (scale 1-5)
ISO 105 B02
5 (scale 1-8)

Naadschuifweerstand
ASTM D4034
26 lbf warp / 26 lbf weft
ISO 13936-2
3.5 mm warp / 3.5 mm weft

Treksterkte
ASTM D5034
73 lbs warp / 76 lbs weft

Keurmerken



Reiniging & Onderhoud



Lamu

7051.01 - 7051.30

7051.01	7051.02	7051.03	7051.04	7051.05	7051.06	7051.07	7051.08	7051.09
7051.10	7051.11	7051.12	7051.13	7051.14	7051.15	7051.16	7051.17	7051.18
7051.19	7051.20	7051.21	7051.22	7051.23	7051.24	7051.25	7051.26	7051.27
7051.28	7051.29	7051.30						