

Lani

7060.01 - 7060.56



Product

Upholstery

Description

Tough, felted wool quality in modern applicable colours

Composition

80% wool / 20% polyamide

Width

± 140 cm, ± 55 inches

Weight

± 640 gr/m², ± 21 oz/yd²

Flame retardancy

**BS 5852 , Crib 5 with FR finish
Cal TB 117-2013, section 1 , Pass
DIN 4102 , B2 with FR finish
EN 1021/1-2 , Pass
IMO 2010 FTP part 8 , Pass with FR finish
NF P 92/503-507 , M2 with FR finish
NFPA 260 , Class 1
UNI 9175 , Classe 1 with FR finish**

Abrasion

**ASTM D3597/D4157 (#10 cotton duck) ,
100.000 double rubs Wyzenbeek
ISO 12947-2 , >300.000 rubs Martindale**

Pilling

**ASTM D3511
2.5 (scale 1-5)
ISO 12945-2
4 (scale 1-5)**

Colorfastness to crocking

AATCC 8

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105 X12

4 - 5 (scale 1-5) wet / 4 - 5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 opt.1 or 16.3 opt. 3

3.5 (scale 1-5)

ISO 105 B02

5-7 (scale 1-8)

Seam slippage

ASTM D4034

125 lbs warp / 116 lbs weft

ISO 13936-2

2.6 mm warp / 3 mm weft

Breaking strength

ASTM D5034

206 lbs warp / 202 lbs weft

Labels



USCG -
EU MRA
0038



STANDARD
100
510-0100
Hohenstein RTT

Care & Maintenance



Lani

7060.01 - 7060.56

7060.01	7060.02	7060.03	7060.04	7060.05	7060.06	7060.07	7060.08	7060.09
7060.10	7060.11	7060.12	7060.13	7060.14	7060.15	7060.16	7060.17	7060.18
7060.19	7060.20	7060.21	7060.22	7060.23	7060.24	7060.25	7060.26	7060.27
7060.28	7060.29	7060.30	7060.31	7060.32	7060.33	7060.34	7060.35	7060.36
7060.37	7060.38	7060.39	7060.40	7060.41	7060.42	7060.43	7060.44	7060.45
7060.46	7060.47	7060.48	7060.49	7060.50	7060.51	7060.52	7060.53	7060.54
7060.55	7060.56							