

Lani

7060.01 - 7060.56



Producto
upholstery

Descripción
Diseño resistente de lana afelpada en colores modernos combinables

Composición
80% lana / 20% poliamida

Anchura
± 140 cm, ± 55 inches

Peso
± 640 gr/m², ± 21 oz/yd²

Combustión retardada
BS 5852 , Crib 5 with FR finish
Cal TB 117-2013, section 1 , Pass
DIN 4102 , B2 with FR finish
EN 1021/1-2 , Pass
IMO 2010 FTP part 8 , Pass with FR finish
NF P 92/503-507 , M2 with FR finish
NFPA 260 , Class 1
UNI 9175 , Classe 1 with FR finish

Resistencia al desgaste
ASTM D3597/D4157 (#10 cotton duck) ,
100.000 double rubs Wyzenbeek
ISO 12947-2 , >300.000 rubs Martindale

Pilling
ASTM D3511
2.5 (scale 1-5)
ISO 12945-2
4 (scale 1-5)

Resistencia al frotamiento
AATCC 8
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105 X12
4 - 5 (scale 1-5) wet / 4 - 5 (scale 1-5) dry

Insensibilidad a la luz
AATCC 16.2 opt.1 or 16.3 opt. 3
3.5 (scale 1-5)
ISO 105 B02
5-7 (scale 1-8)

Resistencia al deslizamiento de costuras
ASTM D4034
125 lbs warp / 116 lbs weft
ISO 13936-2
2.6 mm warp / 3 mm weft

Resistencia a la tensión
ASTM D5034
206 lbs warp / 202 lbs weft

Etiquetas



Cuidado & Mantenimiento



Lani

7060.01 - 7060.56

7060.01 7060.02 7060.03 7060.04 7060.05 7060.06 7060.07 7060.08 7060.09

7060.10 7060.11 7060.12 7060.13 7060.14 7060.15 7060.16 7060.17 7060.18

7060.19 7060.20 7060.21 7060.22 7060.23 7060.24 7060.25 7060.26 7060.27

7060.28 7060.29 7060.30 7060.31 7060.32 7060.33 7060.34 7060.35 7060.36

7060.37 7060.38 7060.39 7060.40 7060.41 7060.42 7060.43 7060.44 7060.45

7060.46 7060.47 7060.48 7060.49 7060.50 7060.51 7060.52 7060.53 7060.54

7060.55 7060.56