

Liran

8054.01 - 8054.15



Producto

curtain

Descripción

Woolly blend look

Composición

100% flame retardant polyester

Anchura

± 143 cm, ± 56 inches

Peso

± 386 gr/m¹, ± 12 oz/yd¹

Absorción del ruido

ISO 354, alpha w

0.85 (pleated)

Confort Visual & Térmico

EN 410/EN 14501

Test available

Combustión retardada

NFPA 701 (meth. 1 or 2) , Pass

EN 13773 , Class 1

BS 5867-2 , Type C

NF P 92/503-507 , M1

DIN 4102 , B1

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

CAN/ULC S109 , Pass

IMO 2010 FTP part 7 , Pass

Resistencia al frotamiento

ISO 105-X12

wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)

AATCC 8 (solids)

wet 5 (scale 1-5) / dry 5 (scale 1-5)

Insensibilidad a la luz

ISO 105-B02

6-7 (scale 1-8)

AATCC 16.2 option 1 or 16.3 opt 3

4 (scale 1-5)

Resistencia al deslizamiento de costuras

ASTM D434 - warp

45 lbs

ASTM D434 - weft

52 lbs

Etiquetas



USCG -
EU MRA
0038

OEKO
TEX®

STANDARD
100
507-0023
Hohenstein HTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

Cuidado & Mantenimiento



Liran

8054.01 - 8054.15

Contracción

Shrinkage 30° - warp

-1.9

Shrinkage 30° - weft

-0.8

Shrinkage 70° - warp

-3.1

Shrinkage 70° - weft

-1.6

Liran

8054.01 - 8054.15
