

Liran

8054.01 - 8054.15



Produit
curtain

Description
Woolly blend look

Composition
100% flame retardant polyester

Largeur
± 143 cm, ± 56 inches

Poids
± 386 gr/m¹, ± 12 oz/yd¹

Absorption acoustique
ISO 354, alpha w
0.85 (pleated)

Confort Visuel & Thermique
EN 410/EN 14501
Test available

Non feu
NFPA 701 (meth. 1 or 2) , Pass
EN 13773 , Class 1
BS 5867-2 , Type C
NF P 92/503-507 , M1
DIN 4102 , B1
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1
CAN/ULC S109 , Pass
IMO 2010 FTP part 7 , Pass

Résistance au frottement

ISO 105-X12
wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)
AATCC 8 (solids)
wet 5 (scale 1-5) / dry 5 (scale 1-5)

Solidité lumière

ISO 105-B02
6-7 (scale 1-8)
AATCC 16.2 option 1 or 16.3 opt 3
4 (scale 1-5)

Résistance au glissement à la couture

ASTM D434 - warp
45 lbs
ASTM D434 - weft
52 lbs

Étiquettes



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI



Baustoffklasse schwerenflammbar
DIN 4102, B1

Entretien & Maintenance



Liran

8054.01 - 8054.15

Rétrécissement

Shrinkage 30° - warp

-1.9

Shrinkage 30° - weft

-0.8

Shrinkage 70° - warp

-3.1

Shrinkage 70° - weft

-1.6

Liran

8054.01 - 8054.15
