


Lucy

8092.01 - 8092.12



Product

Curtain

Description

Acoustic floor-to-ceiling semi-transparent sheer with a soft bouclé yarn in neutral tones, double-sided

Composition

60% recycled polyester FR / 40% polyester FR

Width

± 307 cm, ± 121 inches

Weight

± 494 gr/m¹, ± 15,9 oz/yd¹

Sound absorption

ASTM C423, nrc

0,55

ISO 354, alpha w

0,55

Visual & Thermal comfort

EN 410/EN 14501

Test available

Flame retardancy

BS 5867-2 , Type C

CAN/ULC S109 , Pass

DIN 4102 , B1

EN 13773 , Class 1

IMO 2010 FTP part 7 , Pass

NF P 92/503-507 , M1

NFPA 701 (meth. 1 or 2) , Pass

UNI VF 8456-8457 , Classe 1

Colorfastness to crocking

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 option 1 or 16.3 opt 3

5 (scale 1-5)

ISO 105-B02

6 (scale 1-8)

Seam slippage

ASTM D434

41 warp / 50 weft

ISO 13936-2

2 warp / 2 weft


Labels



USCG -
EU MRA
0038



STANDARD
100
S21-3365
Hohenstein HTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

Care & Maintenance



Shrinkage

Shrinkage 70°

-0,9% warp / -0,5% weft

Lucy

8092.01 - 8092.12



8092.01



8092.02



8092.03



8092.04



8092.05



8092.06



8092.07



8092.08



8092.09



8092.10



8092.11



8092.12