


Mioko

8057.01 - 8057.33



Producto

curtain

Descripción

Satén liso

Composición

100% poliéster ignífugo

Anchura

± 140 cm, ± 56 inches

Peso

± 413 gr/m², ± 12 oz/yd²

Confort Visual & Térmico

EN 410/EN 14501

Test available

Combustión retardada

BS 5867-2 , Type C

CAN/ULC S109 , Pass

DIN 4102 , B1

EN 13773 , Class 1

IMO 2010 FTP part 7 , Pass

NF P 92/503-507 , M1

NFPA 701 (meth. 1 or 2) , Pass

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

Resistencia al frotamiento

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

5 (scale 1-5) wet / 5 (scale 1-5) dry

Insensibilidad a la luz

AATCC 16.2 option 1 or 16.3 opt 3

5 (scale 1-5)

ISO 105-B02

6-7 (scale 1-8)

Resistencia al deslizamiento de costuras

ASTM D434

45.5 lbs warp / 40.5 lbs weft

Etiquetas



Cuidado & Mantenimiento



Contracción

Shrinkage 30°

-1% warp / -0.4% weft

Shrinkage 70°

-1.7% warp / -0.6% weft

Mioko

8057.01 - 8057.33

8057.01	8057.02	8057.03	8057.04	8057.05	8057.06	8057.07	8057.08	8057.09
8057.10	8057.11	8057.12	8057.13	8057.14	8057.15	8057.16	8057.17	8057.18
8057.19	8057.20	8057.21	8057.22	8057.23	8057.24	8057.25	8057.26	8057.27
8057.28	8057.29	8057.30	8057.31	8057.32	8057.33			