

Nila+Print

8064.01



Product

Curtain

Description

Matte, unstructured floor-to-ceiling curtain+print black out

Composition

100% flame retardant polyester acrylic coating

Width

± 280 cm, ± 110 inches

Weight

± 778 gr/m¹, ± 25 oz/yd¹

Visual & Thermal comfort

AATCC 148

Test available

EN 410/EN 14501

Test available

Flame retardancy

BS 5867-2 , Type B

CAN/ULC S109 , Pass

DIN 4102 , B1

EN 13773 , Class 1

IMO 2010 FTP part 7 , Pass

NFPA 701 (meth. 1 or 2) , Pass

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

Colorfastness to crocking

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 option 1 or 16.3 opt 3

4.5 (scale 1-5)

ISO 105-B02


5 (scale 1-8)

Seam slippage

ASTM D434

48 lbs warp / 53 lbs weft

Labels



Care & Maintenance



Shrinkage

Shrinkage 30°

-1% warp / -0.5% weft

Shrinkage 70°

-1.2% warp / -0.4% weft

Nila+Print

8064.01

8064.01