

Noss

7058.01 - 7058.24



Product

Upholstery

Description

Woven chenille blended in soft colours

Composition

100% flame retardant polyester

Width

± 140 cm, ± 55 inches

Weight

± 904 gr/m², ± 29 oz/yd²

Flame retardancy

BS 5852 , Crib 5

Cal TB 117-2013, section 1 , Pass

DIN 4102 , B1

EN 1021/1-2 , Pass

IMO 2010 FTP part 8 , Pass

NF P 92/503-507 , M1

NFPA 260 , Class 1

Abrasion

**ASTM D3597/D4157 (#10 cotton duck) ,
90.000 double rubs Wyzenbeek**

ISO 12947-2 , 70.000 rubs Martindale

Pilling

ASTM D3511

5 (scale 1-5)

ISO 12945-2

4 (scale 1-5)

Colorfastness to crocking

AATCC 8

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105 X12

4 - 5 (scale 1-5) wet / 4 - 5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 opt.1 or 16.3 opt. 3

5 (scale 1-5)

ISO 105 B02

6 - 7 (scale 1-8)

Seam slippage

ASTM D4034

77 lbs warp / 91 lbs weft

ISO 13936-2

3.3 mm warp / 3 mm weft

Breaking strength

ASTM D5034

524 lbs warp / 337 lbs weft

Labels



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI

Care & Maintenance



Shrinkage

Shrinkage 30°

-1.5% warp / -1.7% weft

Shrinkage 70°

-1.6% warp / -3% weft

Noss

7058.01 - 7058.24

7058.05 7058.06 7058.07 7058.08 7058.09 7058.10 7058.11 7058.12 7058.13

7058.14 7058.15 7058.16 7058.17 7058.18 7058.19 7058.20 7058.21 7058.22

7058.23 7058.24