

Noss

7058.01 - 7058.24



产品

upholstery

描述

软色调混编绳绒面料

成分

100%特弗拉阻燃纤维

宽幅

± 140 cm, ± 55 inches

重量

± 904 gr/m², ± 29 oz/yd²

阻燃

BS 5852 , Crib 5
Cal TB 117-2013, section 1 , Pass
DIN 4102 , B1
EN 1021/1-2 , Pass
IMO 2010 FTP part 8 , Pass
NF P 92/503-507 , M1
NFPA 260 , Class 1

耐磨性

ASTM D3597/D4157 (#10 cotton duck) ,
90.000 double rubs Wyzenbeek
ISO 12947-2 , 70.000 rubs Martindale

起毛指数

ASTM D3511
5 (scale 1-5)
ISO 12945-2
4 (scale 1-5)

耐摩擦褪色

AATCC 8
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105 X12
4 - 5 (scale 1-5) wet / 4 - 5 (scale 1-5) dry

耐光照褪色

AATCC 16.2 opt.1 or 16.3 opt. 3
5 (scale 1-5)
ISO 105 B02
6 - 7 (scale 1-8)

耐滑缝

ASTM D4034
77 lbs warp / 91 lbs weft
ISO 13936-2
3.3 mm warp / 3 mm weft

抗断裂强度

ASTM D5034
524 lbs warp / 337 lbs weft

标签



保养与维护



收缩率

Shrinkage 30°
-1.5% warp / -1.7% weft
Shrinkage 70°
-1.6% warp / -3% weft

Noss

7058.01 - 7058.24

7058.01 7058.03 7058.05 7058.06 7058.07 7058.08 7058.09 7058.10 7058.11

7058.12 7058.13 7058.14 7058.15 7058.16 7058.17 7058.18 7058.19 7058.20

7058.21 7058.22 7058.23 7058.24