

Rani

8067.01 - 8067.22



Product

curtain

Omschrijving

Weefstructuur met linnen look, dim out

Samenstelling

100% brandvertragend polyester

Breedte

± 294 cm, ± 116 inches

Gewicht

± 861 gr/m¹, ± 28 oz/yd¹

Visueel & Thermisch comfort

AATCC 148

Test available

EN 410/EN 14501

Test available

Brandwerendheid

BS 5867-2 , Type C

CAN/ULC S109 , Pass

DIN 4102 , B1

EN 13773 , Class 1

IMO 2010 FTP part 7 , Pass

NF P 92/503-507 , M1

NFPA 701 (meth. 1 or 2) , Pass

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

Wrijfechtheid

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Lichtechtheid

AATCC 16.2 option 1 or 16.3 opt 3

2.5 (scale 1-5)

ISO 105-B02

5 (scale 1-8)

Naadschuifweerstand

ASTM D434

53.5 lbs warp / 48 lbs weft


Keurmerken



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

Reiniging & Onderhoud



Krimp

Shrinkage 30°

-0.8% warp / -0.4% weft

Shrinkage 70°

-1.6% warp / -0.7% weft

Rani

8067.01 - 8067.22

8067.01	8067.02	8067.03	8067.04	8067.05	8067.06	8067.07	8067.08	8067.09
8067.10	8067.11	8067.12	8067.13	8067.14	8067.15	8067.16	8067.17	8067.18
8067.19	8067.20	8067.21	8067.22					