

Rolla

7065.01 - 7065.20



Product

Upholstery

Description

Upholstery fabric with a bold 3D graphic pattern

Composition

88% recycled polyester FR / 12% polyester FR

Width

± 140 cm, ± 55 inches

Weight

± 775 gr/m¹, ± 25 oz/yd¹

Flame retardancy

**BS 5852 , Crib 5
Cal TB 117-2013, section 1 , Pass
DIN 4102 , B1
EN 1021/1-2 , Pass
IMO 2010 FTP part 8 , Pass
NF P 92/503-507 , M1
NFPA 260 , Class 1**

Abrasion

**ASTM D3597/D4157 (#10 cotton duck) ,
100.000 double rubs Wyzenbeek
ISO 12947-2 , 50.000 rubs Martindale**

Pilling

**ASTM D3511
3 (scale 1-5)
ISO 12945-2
4 (scale 1-5)**

Colorfastness to crocking

AATCC 8

5 (scale 1-5) wet / 4.5 (scale 1-5) dry

ISO 105 X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 opt.1 or 16.3 opt. 3

4 (scale 1-5)

ISO 105 B02

6 (scale 1-8)

Seam slippage

ASTM D4034

102 lbs warp / 83 lbs weft

ISO 13936-2

2.3 mm warp / 2 mm weft

Breaking strength

ASTM D5034

239 lbs warp / 560 lbs weft

ISO 13934-1

1120 N warp / 2500 N weft

Labels



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI

Care & Maintenance



Shrinkage

Shrinkage 70°

-2.8% warp / -2.6% weft

Rolla

7065.01 - 7065.20

7065.01	7065.02	7065.03	7065.04	7065.05	7065.06	7065.07	7065.08	7065.09
7065.10	7065.11	7065.12	7065.13	7065.14	7065.16	7065.17	7065.18	7065.19
7065.20	7065.15							