

Sotra

8070.01 - 8070.24



Produkt
curtain

Beschreibung
**Vorhangstoff in natürlicher Seidenoptik,
Black-Out**

Zusammensetzung
**100% flame retardant polyester acrylic
coating**

Breite
± 283 cm, ± 111 inches

Gewicht
± 778 gr/m¹, ± 25 oz/yd¹

Schallabsorption
**ISO 354, alpha w
0.35**

Visueller und thermischer Komfort
AATCC 148
Test available
EN 410/EN 14501
Test available


Brandschutzklasse
**BS 5867-2 , Type B
CAN/ULC S109 , Pass
DIN 4102 , B1
EN 13773 , Class 1
IMO 2010 FTP part 7 , Pass
NFPA 701 (meth. 1 or 2) , Pass
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1**

Farbechtheit
AATCC 8 (solids)
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105-X12
4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Lichtechtheit
AATCC 16.2 option 1 or 16.3 opt 3
4.5 (scale 1-5)
ISO 105-B02
5 (scale 1-8)

Schiebewiderstand
ASTM D434
48 lbs warp / 53 lbs weft

Labels



Pflege & Instandhaltung



Schrumpfung
Shrinkage 30°
-1% warp / -0.5% weft
Shrinkage 70°
-1.2% warp / -0.4% weft

Sotra

8070.01 - 8070.24

8070.01	8070.02	8070.03	8070.04	8070.05	8070.06	8070.07	8070.08	8070.09
8070.10	8070.11	8070.12	8070.13	8070.14	8070.15	8070.16	8070.17	8070.18
8070.19	8070.20	8070.21	8070.22	8070.23	8070.24			