

Sotra

8070.01 - 8070.24



Product

Curtain

Description

Natural silk look curtain fabric, black-out

Composition

100% flame retardant polyester acrylic coating

Width

± 283 cm, ± 111 inches

Weight

± 778 gr/m¹, ± 25 oz/yd¹

Sound absorption

ISO 354, alpha w
0.35

Visual & Thermal comfort

AATCC 148

Test available

EN 410/EN 14501

Test available

Flame retardancy

BS 5867-2 , Type B
CAN/ULC S109 , Pass
DIN 4102 , B1

EN 13773 , Class 1
IMO 2010 FTP part 7 , Pass
NFPA 701 (meth. 1 or 2) , Pass
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1

Colorfastness to crocking

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 option 1 or 16.3 opt 3

4.5 (scale 1-5)

ISO 105-B02


5 (scale 1-8)

Seam slippage

ASTM D434

48 lbs warp / 53 lbs weft

Labels



Care & Maintenance



Shrinkage

Shrinkage 30°

-1% warp / -0.5% weft

Shrinkage 70°

-1.2% warp / -0.4% weft

Sotra

8070.01 - 8070.24

8070.01	8070.02	8070.03	8070.04	8070.05	8070.06	8070.07	8070.08	8070.09
8070.10	8070.11	8070.12	8070.13	8070.14	8070.15	8070.16	8070.17	8070.18
8070.19	8070.20	8070.21	8070.22	8070.23	8070.24			