

Tula

8081.01 - 8081.16



Product
curtain

Omschrijving

Subtiel gekleurde melange structuur in een droge, wollige look en feel

Samenstelling

60% recycled polyester FR / 40% polyester FR

Breedte

± 149 cm, ± 59 inches

Gewicht

± 395 gr/m¹, ± 13 oz/yd¹

Geluidsabsorptie

ISO 354, alpha w
0.75 (pleated)

Visueel & Thermisch comfort

EN 410/EN 14501

Test available

Brandwerendheid

BS 5867-2 , Type C
CAN/ULC S109 , Pass
DIN 4102 , B1
EN 13773 , Class 1
IMO 2010 FTP part 7 , Pass
NF P 92/503-507 , M1
NFPA 701 (meth. 1 or 2) , Pass
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1

Wrijfechtheid

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Lichtechtheid

AATCC 16.2 option 1 or 16.3 opt 3

5 (scale 1-5)

ISO 105-B02

6 (scale 1-8)

Naadschuifweerstand

ASTM D434

49 lbs warp / 51 lbs weft

ISO 13936-2

3 mm warp / 4.7 mm weft


Keurmerken



USCG -
EU MRA
0038



STANDARD
100
S07-0023
Hohenstein HTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

Reiniging & Onderhoud



Krimp

Shrinkage 70°

-2% warp / -1.6% weft

Tula

8081.01 - 8081.16

8081.01	8081.02	8081.03	8081.04	8081.05	8081.06	8081.07	8081.08	8081.09
8081.10	8081.11	8081.12	8081.13	8081.14	8081.15	8081.16		